

REMARKS/ARGUMENTS

Favorable reconsideration of this application, as presently amended and in light of the following discussion, is respectfully requested.

Claims 1 and 3-6 are pending in the application. Claim 1 is amended by the present amendment. Support for amended Claim 1 can be found in the original specification, claims and drawings.<sup>1</sup> No new matter is presented.

In the outstanding Office Action, Claims 1 and 3-6 were rejected under 35 U.S.C. § 103(a) as unpatentable over Hongo et al. (U.S. Pub. 2003/0053552, herein Hongo) in view of Wright et al. (U.S. Pat. 7,260,365, herein Wright).

In response to the rejection based on Hongo and Wright, Applicants respectfully submit that independent Claim 1 recites novel features clearly not taught or rendered obvious by the applied references.

Amended independent Claim 1 relates to a transmitter which detects distortion components produced by a power amplifier, and uses the detected distortion components in predistorters to produce a compensation signal to cancel the distortion components at the power amplifiers.

As described in an exemplary embodiment at Fig. 4, the claimed transmitter includes an input-side digital multi-port directional coupler 13 configured to divide and combine digital transmission signals of N-channels, and output N-combined signals to N transmission paths. N predistorters 21 are inserted in the N transmission paths, respectively, and provide compensating predistortions to the N-combined signals outputted from the input-side digital multi-port directional coupler 13. The transmitter also includes N transmitting parts 30, which are inserted in the N transmission paths, respectively, and convert output signals from the N predistorters 21 to N high-frequency signals, each of the N transmitting parts including

---

<sup>1</sup> e.g., specification, p. 3, ll. 2-11.

a power amplifier 33 for amplifying power of the high-frequency signal. An output-side multi-port power combiner 40 divides and combines the N high-frequency signals to output N high-frequency transmission signals. N receiving parts 50 are configured to extract, from said N high-frequency signals, distortion components produced by the power amplifiers and generate, based on said distortion components, compensating signals which control said N predistorters. Based on the compensating signals, N predistorters generate compensating predistortions and impart said compensating predistortions to said N-combined signals from said input-side digital multi-port directional coupler, respectively, to cancel the distortion components at said power amplifiers.

Turning to the applied references, Hongo, the primary reference, describes a distortion compensator used to compensate for distortion produced in an amplifier.

Hongo, however, fails to disclose the use of either the input-side multi-port directional coupler or output-side multi-port directional coupler, as recited in independent Claim 1.

In Hongo, an input signal containing signals of a plurality of different frequency bands is frequency-divided into respective frequency-band signals by a frequency band divider 1, each of the frequency band signals is subjected to predistortion by a distortion compensator 2, and then the plural predistorted frequency band signals are combined by a frequency band combiner 3 into a combined signal which in turn is amplified by an amplifier 4. It is apparent that the frequency band divider acts as a filter for separating plural frequency band signals from one another.

Thus, in Hongo, an amplifier is not provided on any of the predistortion paths for frequency-band-divided signals, rather an amplifier is provided on a combined signal path on the output side of the frequency band combiner 3. The function of the frequency band divider 1 in Hongo completely differs from that of the input-side multi-port directional coupler, as recited in independent Claim 1.

In the present invention, the input-side multi-port directional coupler distributes an input signal at each of its N input ports to its N output ports and the N distributed signals at each output port are outputted as a combined signal to corresponding one of the N transmission paths between the input-side multi-port directional coupler 13 and the output-side multi-port directional coupler 40. As explained previously, since the input-side multi-port directional coupler 13 distributes an input signal at each of N input ports of the coupler to N output ports of the coupler, a signal on each transmission path contains all components of the N input signals. The function of the multi-port directional coupler itself is well known to those skilled in the art. According to the present invention, the signal on each of the N transmission paths is subjected to predistortion and then supplied to the power amplifier, the outputs of the amplifiers on the N transmission paths are supplied to the output-side multi-port directional coupler 40.

The function of the output-side multi-port directional coupler 40 is substantially similar to that of the input-side multi-port directional coupler 13 as described in an exemplary embodiment at Figs. 2A and 2B and their corresponding description. That is, a signal at each of N input ports of the coupler 13 is distributed to N output ports of the coupler 13, thus outputting a combined signal from each output port. As explained in the present specification, each of the signals from the N output ports of the coupler 40 corresponds to one of the N input signals at the N input ports of the coupler 13.

Accordingly, the claimed multi-port directional coupler completely differs from either frequency band divider or frequency band combiner employed in Hongo. More specifically, Hongo fails to teach or suggest a transmitter comprising “an input-side digital multi-port directional Butler matrix coupler configured to divide and combine digital transmission signals of N channels by digital processing and configured to output N-combined signals to N transmission paths, respectively... and an output-side multi-port Butler matrix directional

coupler configured to divide and combine said N high-frequency signals to output N high-frequency transmission signals,” as recited in independent Claim 1.

Wright, the secondary reference, relates to a digital predistortion linearizer, wherein a digital baseband signal is subjected to predistortion and then to DA conversion, and the resultant analog predistorted baseband signal is up-converted and then supplied to an amplifier. The output of the amplifier is down-converted to a baseband signal which in turn is converted to a digital signal to be used for controlling the predistortion, thereby compensating for a distortion produced by the amplifier.


Wright, however, does not disclose any multi-port configuration and therefore fails to cure the above noted deficiencies of Hongo.

Accordingly, for at least the reasons discussed above, Applicants respectfully request the rejection of Claims 1 and 3-6 under 35 U.S.C. § 103 be withdrawn.

Consequently, in view of the present amendment and in light of the foregoing comments, it is respectfully submitted that the invention defined by Claims 1 and 3-6 is patentably distinguishing over the applied references. The present application is therefore believed to be in condition for formal allowance and an early and favorable action is therefore requested.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,  
MAIER & NEUSTADT, P.C.



---

Bradley D. Lytle  
Attorney of Record  
Registration No. 40,073

Andrew T. Harry  
Registration No. 56,959

Customer Number  
**22850**

Tel: (703) 413-3000  
Fax: (703) 413 -2220  
(OSMMN 06/04)

BDL:ATH\mms

I:\ATTY\ATH\PROSECUTION\24'S\241973US\241973US - AM DUE 01-24-08.DOC